Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2020-04-16

Section 1 - Product and Company Information

Product Name: Bumper and Cladding Color Coat - White Toner

Product Part Number(s): 3702-1,

Recommended Use: Low VOC Bumper Coating Color Coat

COMPANY IDENTIFICATION: EMERGENCY TELEPHONE NUMBER:

Polyvance **24 Hour Emergency contact:** Chemtrec: 1-800-424-9300

1128 Kirk Rd. Outside US: 703-527-3887

Rainsville, AL 35986

Information email: info@polyvance.com Customer Information Number: 256-638-4103 (7AM - 4PM (CST) M-F)

Section 2 - Hazards Identification

Appearance: White pourable liquid

Odor: Not available

Hazard Statement:

WARNING! . Flammable liquid and vapor. May be harmful if

swallowed. May cause an allergic skin reaction.

Signal Word: WARNING!

Signal Word Hazard: Flammable Liquid

GHS Physical Hazard Pictogram



Flammable

GHS Health Hazard Pictogram(s)



Irritant

GHS Environmental Hazard Pictogram

Not Applicable

GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Health	H317	May cause an allergic skin reaction
Physical	H226	Flammable liquid and vapor
Health	H303	May be harmful if swallowed

Precautionary Statement:

Keep out of reach of children. Read label before use. IF ON SKIN: Wash with soap and water. Remove/Take off immediately all contaminated clothing.

GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
General	P102	Keep out of reach of children
General	P103	Read label before use
Response	P302+352	IF ON SKIN: Wash with soap and water

Remove/Take off immediately all contaminated clothing

Potential Health Effects

P361

Response

Eye Contact: Moderate irritation, redness, blurred vision.

Skin Contact: Moderate irritation, redness, dermatitis.

Inhalation: Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and

asphyxiation.

Ingestion: Gastrointestinal irritation, vomiting, diarrhea.

Section 3 - Composition / Information on Ingredients

Component	CAS#	ENIECS	REACH Reg. No.	Amount
Xylene	1330-20-7			5 - 7%
PM Acetate	108-65-6			1 - 3%
Parachlorobenzotriflouride (PCBTF)	98-56-6			20 - 25%
Acteone	67-64-1			5 - 10%
Aromatic Naphtha	64742-94-5			1 - 5%
Dibutyl Phthalate	87-74-2			1 - 3%
Methyl Acetate	79-20-9			25 - 30%
Acrylic polymer	Blend			10 - 15%

Section 4 - First Aid Measures

Eye Contact: Immediately wash out with plenty of water with the eyelid held wide open.

Skin Contact: Remove contaminated clothing. Wash contaminated skin with soap and water.

Inhalation: Remove victim to fresh air.

Ingestion: Rinse mouth. Do not induce vomiting.

Medical Conditions
Aggravated by

Exposure:

Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged exposure to the substance can product lung damage. Repeated or prolonged contact with spray or

mist may produce chronic eye irritation and severe skin irritation

Section 5 - Firefighting Measures

Extinguishing Media: SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray, fog, or foam. Do not use

water jet.

Special Protective Equipment:

In case of fire and/or explosion, do not breathe fumes. A self-contained breathing apparatus should

be used to avoid inhalation of the product.

Hazardous Combustion

These products are carbon oxides (CO, CO2), nitrogen oxides (NO, NO2, etc.

Products:

Section 6 - Accidental Release Measures

Personal Precautions: Use personal protective equipment as described in section 8. Ventilation recommended.

Environmental

Do not allow to enter sewage system

Precautions:

Section 7 - Handling and Storage

General Handling Avoid contact with skin and eyes. Use only in well-ventilated areas. Handle and open container **Practices:**

with care. Do not breathe gas/fumes/vapor/spray. Local exhaust required. Use personal protective

equipment described in section 8

Handling Precautions: Wear gloves, goggles and protective clothing to prevent contact with product.

Storage Requirements: Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep away from

heat. Keep from freezing. Store material at temperatures between 36F and 120F. Do not store

containers in direct sunlight

Section 8 - Precautions to Control Exposure / Personal Protection

Component	Source	Туре	Value	Remarks
Acteone	OSHA	TWA	1000 ppm	
Acteone	ACGIH	TWA	500 ppm	
Dibutyl Phthalate	OSHA	TLV	5 mg/m3	TWA
Dibutyl Phthalate	ACGIH	PEL	5 mg/m3	TWA
Methyl Acetate	ACGIH	TLV	250 ppm	STEL
Methyl Acetate	ACGIH	TLV	200 ppm	TWA
Methyl Acetate	OSHA	PEL	200 ppm	TWA
Parachlorobenzotriflouride (PCBTF)	Manufacturer	TWA	20 ppm	
Xylene	OSHA	PEL	100 ppm	TWA
Xylene	ACGIH	TLV	100 ppm	TWA
Xylene	ACGIH	TLV	150 ppm	STEL

Personal Protective Equipment (PPE):

Eye / Face Protection: Chemical splash goggles (ANSI Z 87.1 or approved equivalent.

Skin Protection: Impervious rubber gloves.

G

In case of insufficient ventilation, wear suitable respiratory equipment. **RespiratoryProtection:**

Wash hands before eating, smoking or using the bathroom. **Hygenic Measures:**

Engineering Controls: Adequate to keep exposure limits below those listed in section II

HMIS Personal

Protection:







Section 9 - Physical and Chemical Properties

Appearance: Liquid

Color: White

Odor: Fruity odor

Odor Threshold: Not determined

pH: Not determined

Melting Point: Not available Freezing Point: Not available **Boiling Point:** Not available Boiling Range: Not available **Flash Point:** 21 C (69 F)

Evaporation Rate: Faster than n-Butyl Acetate

Flammability: Not available

Upper Flammability Limit: Not available **Lower Flammability Limit:** Not available

Vapor Pressure: Not availableVapor Density: Heavier than air

Specific Gravity: 1.07

Solubility in Water: Not available
Partition Coefficient: Not available
Autoignition Temperature: Not available
Decomposition Temperature: Not available

Viscosity: Not available

Percent Volitiles: 75 - 80%

Volitile Organic Compounds 334 g/l (2.79 lb./gal)

(VOC's):

Section 10 - Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Excessive heat and freezing temperatures

Incompatible Materials: Oxidizing agents, alkalis and high temperatures.

Hazardous Decomposition Chlorine, hydrogen chloride (hydrochloric acid), phosgene

Products:

Hazardous Polymerization: Will not occur

Section 11 - Toxicological Information

Sensitization: No sensitizing effects known

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Disposal Method: Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do

not contaminate lakes, streams or other water supply.

ContainerDisposal: Disposal must be made according to official

regulations

Section 14 - Transport Information

DOT

Proper Shipping Name: Paint

Hazard Class: 3

Identification Number: UN1263

Packing Group: II

IMDG (Maritime transport)

Proper Shipping Name: Paint

IMDG Class: 3

UN Number: UN1263

Label: 3

EMS Number: F-E, S-E

Marine Polutant?: No

IATA (Air transport)

Proper Shipping Name: Paint

ICAO / IATA Class: 3

UN / ID Number: UN1263

Label: 3

Packing Group ||

Section 15 - Regulatory Information

Superfund Amendments and Reathorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986)

Sections 311 and 312

Immediate (Acute) Health Hazard: Not available Delayed (Chronic) Health Hazard: Not available Fire Hazard: Not available Reactive Hazard: Not available Sudden Realease of Pressure: Not available

The following lists hazardous components and the regulatory lists for which they are required to be reported.

Component: Acteone

CAS: 67-64-1 **Amount:** 5 - 10%

Acteone is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.

Component: Dibutyl Phthalate

CAS: 87-74-2 **Amount:** 1 - 3%

Dibutyl Phthalate is on the California Prop 65 Cancer list.


Component: Xylene CAS: 1330-20-7 Amount: 5 - 7%

Xylene is listed with Pennsylvania Right to Know.


Xylene is listed with the Envronmental Protection Agency (EPA) as a possible carcinogen.

Xylene is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.

HMIS Rating (0 - 4)



NFPA Ratings



Section 16 - Other Information

Legend

ACGIH

	780
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations
EPA	Environmental Protection Agency
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
LTEL	Long Term Exposure Limit
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OEL	Occupational Exposure Limit

American Conference of Governmental Hygenists

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
REL Recommended Exposure Level

SARA Superfund Amendment and Reauthorization Act

STEL Short Term Exposure Limit
TLV Threshold Limit Value

TSCA Toxic Substances Control Act
TWA Time Weighted Average
VOC Volitile Organic Compounds

DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein my be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.