

1 Identification

- **Product identifier**
- **Trade name:** 39853 Texture Coating
- **Article number:** 39853
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 2 H371 May cause damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 39853 Texture Coating

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
ethylbenzene
acetone

· **Hazard statements**

H222 *Extremely flammable aerosol.*
H280 *Contains gas under pressure; may explode if heated.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H350 *May cause cancer.*
H361 *Suspected of damaging fertility or the unborn child.*
H371 *May cause damage to organs.*
H336 *May cause drowsiness or dizziness.*
H373 *May cause damage to organs through prolonged or repeated exposure.*
H304 *May be fatal if swallowed and enters airways.*

· **Precautionary statements**

P201 *Obtain special instructions before use.*
P202 *Do not handle until all safety precautions have been read and understood.*
P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Pressurized container: Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P264 *Wash thoroughly after handling.*
P270 *Do not eat, drink or smoke when using this product.*
P280 *Wear protective gloves/protective clothing/eye protection/face protection.*
P301+P310 *If swallowed: Immediately call a poison center/doctor.*
P321 *Specific treatment (see on this label).*
P331 *Do NOT induce vomiting.*
P302+P352 *If on skin: Wash with plenty of water.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

P308+P313 *IF exposed or concerned: Get medical advice/attention.*
P314 *Get medical advice/attention if you feel unwell.*
P362+P364 *Take off contaminated clothing and wash it before reuse.*
P332+P313 *If skin irritation occurs: Get medical advice/attention.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P405 *Store locked up.*
P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

Trade name: 39853 Texture Coating

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
108-88-3	toluene	13-30%
14808-60-7	Quartz (SiO ₂)	13-30%
67-64-1	acetone	10-13%
14807-96-6	Talc	≥7-<10%
78-93-3	butanone	5-7%
108-65-6	2-methoxy-1-methylethyl acetate	1.5-5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

USA

(Contd. on page 4)



Trade name: 39853 Texture Coating

(Contd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

108-88-3	toluene	67 ppm
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
67-64-1	acetone	200 ppm
78-93-3	butanone	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1333-86-4	Carbon black	9 mg/m ³
1330-20-7	xylene	130 ppm
112945-52-5	SILICA	18 mg/m ³
111-76-2	2-butoxyethanol	60 ppm
123-86-4	n-butyl acetate	5 ppm
67-56-1	methanol	530 ppm
100-41-4	ethylbenzene	33 ppm
57-55-6	Propylene glycol	30 mg/m ³
78-83-1	butanol	150 ppm

· PAC-2:

108-88-3	toluene	560 ppm
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
67-64-1	acetone	3200* ppm
78-93-3	butanone	2700* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1333-86-4	Carbon black	99 mg/m ³
1330-20-7	xylene	920* ppm

(Contd. on page 5)



Trade name: 39853 Texture Coating

(Contd. of page 4)

112945-52-5	SILICA	100 mg/m ³
111-76-2	2-butoxyethanol	120 ppm
123-86-4	n-butyl acetate	200 ppm
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
57-55-6	Propylene glycol	1,300 mg/m ³
78-83-1	butanol	1,300 ppm
· PAC-3:		
108-88-3	toluene	3700* ppm
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
67-64-1	acetone	5700* ppm
78-93-3	butanone	4000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1333-86-4	Carbon black	590 mg/m ³
1330-20-7	xylene	2500* ppm
112945-52-5	SILICA	630 mg/m ³
111-76-2	2-butoxyethanol	700 ppm
123-86-4	n-butyl acetate	3000* ppm
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm
57-55-6	Propylene glycol	7,900 mg/m ³
78-83-1	butanol	8000* ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 6)



Trade name: 39853 Texture Coating

(Contd. of page 5)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI

78-93-3 butanone

PEL	Long-term value: 590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 7)

Trade name: 39853 Texture Coating

(Contd. of page 6)

· Ingredients with biological limit values:

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

78-93-3 butanone

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)



Trade name: 39853 Texture Coating

(Contd. of page 7)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55.8-56.6 °C

- **Flash point:** -103 °C

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 514 °C

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

- **Explosion limits:**

Lower:	1.2 Vol %
Upper:	7 Vol %

- **Vapor pressure at 20 °C:** 29 hPa

Density at 20 °C:	0.87461 g/cm ³
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

(Contd. on page 9)



Trade name: 39853 Texture Coating

(Contd. of page 8)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 66.3 %
 - Water:** 0.0 %
 - VOC content:** 55.34 %
551.2 g/l / 4.60 lb/gl
- **Solids content:** 33.6 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
14808-60-7	Quartz (SiO ₂)	1
14807-96-6	Talc	3
1333-86-4	Carbon black	2B

(Contd. on page 10)



Trade name: 39853 Texture Coating

(Contd. of page 9)

1330-20-7	xylene	3
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K
· OSHA-Ca (Occupational Safety & Health Administration)		
68911-87-5	montmorilontie clay complex	

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1950
· UN proper shipping name	
· DOT	Aerosols, flammable
· ADR	1950 Aerosols
· IMDG	AEROSOLS
· IATA	AEROSOLS, flammable

(Contd. on page 11)

Trade name: 39853 Texture Coating

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1
· **Label** 2.1

· **ADR**



· **Class** 2 5F Gases
· **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
· **Label** 2.1

· **Packing group**
· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:**
· **Marine pollutant:** No

· **Special precautions for user** Warning: Gases
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
· **Quantity limitations** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

(Contd. on page 12)



Trade name: 39853 Texture Coating

(Contd. of page 11)

· ADR	
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3	toluene
	Acrylic Resin
14807-96-6	Talc
78-93-3	butanone
1330-20-7	xylene
111-76-2	2-butoxyethanol
67-56-1	methanol
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

108-88-3	toluene
14808-60-7	Quartz (SiO ₂)
67-64-1	acetone
14807-96-6	Talc
78-93-3	butanone
108-65-6	2-methoxy-1-methylethyl acetate
68911-87-5	montmorilontie clay complex
16883-83-3	benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
1333-86-4	Carbon black
1330-20-7	xylene
111-76-2	2-butoxyethanol
123-86-4	n-butyl acetate
67-56-1	methanol
100-41-4	ethylbenzene
57-55-6	Propylene glycol
78-83-1	butanol

(Contd. on page 13)

USA



Trade name: 39853 Texture Coating

(Contd. of page 12)

7732-18-5	water
-----------	-------

· **TSCA new (21st Century Act) (Substances not listed)**

68476-86-8	Petroleum gases, liquefied, sweetened
------------	---------------------------------------

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

1333-86-4	Carbon black
-----------	--------------

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

67-56-1	methanol
---------	----------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
----------	---------	----

67-64-1	acetone	I
---------	---------	---

78-93-3	butanone	I
---------	----------	---

1330-20-7	xylene	I
-----------	--------	---

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

100-41-4	ethylbenzene	D
----------	--------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
----------	---------	----

14808-60-7	Quartz (SiO ₂)	A2
------------	----------------------------	----

67-64-1	acetone	A4
---------	---------	----

14807-96-6	Talc	A4
------------	------	----

1333-86-4	Carbon black	A4
-----------	--------------	----

1330-20-7	xylene	A4
-----------	--------	----

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

1333-86-4	Carbon black
-----------	--------------

67-56-1	methanol
---------	----------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)



Trade name: 39853 Texture Coating

(Contd. of page 13)

· Hazard pictograms



GHS02 GHS04 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

*Quartz (SiO₂)**toluene**ethylbenzene**acetone*

· Hazard statements

*H222 Extremely flammable aerosol.**H280 Contains gas under pressure; may explode if heated.**H315 Causes skin irritation.**H319 Causes serious eye irritation.**H350 May cause cancer.**H361 Suspected of damaging fertility or the unborn child.**H371 May cause damage to organs.**H336 May cause drowsiness or dizziness.**H373 May cause damage to organs through prolonged or repeated exposure.**H304 May be fatal if swallowed and enters airways.*

· Precautionary statements

*P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Pressurized container: Do not pierce or burn, even after use.**P260 Do not breathe dust/fume/gas/mist/vapors/spray.**P264 Wash thoroughly after handling.**P270 Do not eat, drink or smoke when using this product.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P301+P310 If swallowed: Immediately call a poison center/doctor.**P321 Specific treatment (see on this label).**P331 Do NOT induce vomiting.**P302+P352 If on skin: Wash with plenty of water.**P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P314 Get medical advice/attention if you feel unwell.**P362+P364 Take off contaminated clothing and wash it before reuse.**P332+P313 If skin irritation occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P405 Store locked up.**P410+P403 Protect from sunlight. Store in a well-ventilated place.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 15)

Trade name: 39853 Texture Coating

(Contd. of page 14)

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Rita Joiner (rjoiner@semproducts.com)
- **Date of preparation / last revision** 05/21/2018 / 11
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Compressed gas
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 1A: Carcinogenicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 2: Specific target organ toxicity (single exposure) – Category 2
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
- *** Data compared to the previous version altered.**