

# Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2020-04-16

## Section 1 - Product and Company Information

**Product Name:** Bumper and Cladding Color Coat - Black Toner

**Product Part Number(s):** 3701-4,

**Recommended Use:** Low VOC Bumper Coating Color Coat

**COMPANY IDENTIFICATION:**

Polyvance  
1128 Kirk Rd.  
Rainsville, AL 35986

**Information email:** info@polyvance.com

**EMERGENCY TELEPHONE NUMBER:**

**24 Hour Emergency contact:** Chemtrec: 1-800-424-9300  
Outside US: 703-527-3887

**Customer Information Number:** 256-638-4103 (7AM - 4PM (CST) M-F)

## Section 2 - Hazards Identification

**Appearance:** Black pourable liquid

**Odor:** Not available

**Hazard Statement:**

WARNING! Flammable gas. Heating may cause a fire or explosion.  
May be harmful if swallowed. May be harmful in contact with skin.

**Signal Word:** WARNING!

**Signal Word Hazard:** Flammable Liquid

GHS Physical Hazard Pictogram	GHS Health Hazard Pictogram(s)	GHS Environmental Hazard Pictogram
 Flammable	 Irritant	Not Applicable

### GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Health	H303	May be harmful if swallowed
Health	H313	May be harmful in contact with skin
Physical	H221	Flammable gas
Physical	H241	Heating may cause a fire or explosion

**Precautionary Statement:**

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Do not get in eyes, on skin, or on clothing. IF ON SKIN: Gently wash with soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

### GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
General	P102	Keep out of reach of children
General	P103	Read label before use
Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
Prevention	P262	Do not get in eyes, on skin, or on clothing
Response	P302+350	IF ON SKIN: Gently wash with soap and water
Response	P305+351+33	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing

## Potential Health Effects

<b>Eye Contact:</b>	Moderate irritation, redness, blurred vision.
<b>Skin Contact:</b>	Moderate irritation, redness, dermatitis.
<b>Inhalation:</b>	Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and asphyxiation.
<b>Ingestion:</b>	Gastrointestinal irritation, vomiting, diarrhea.

## Section 3 - Composition / Information on Ingredients

Component	CAS #	ENIECS	REACH Reg. No.	Amount
Xylene	1330-20-7			5 - 7%
PM Acetate	108-65-6			1 - 5%
Parachlorobenzotrifluoride (PCBTF)	98-56-6			20 - 25%
Acetone	67-64-1			5 - 10%
Aromatic Naphtha	64742-94-5			1 - 5%
Dibutyl Phthalate	87-74-2			1 - 5%
Methyl Acetate	79-20-9			25 - 30%
Acrylic polymer	Blend			15 - 20%

## Section 4 - First Aid Measures

<b>Eye Contact:</b>	Immediately wash out with plenty of water with the eyelid held wide open.
<b>Skin Contact:</b>	Remove contaminated clothing. Wash contaminated skin with soap and water.
<b>Inhalation:</b>	Remove victim to fresh air.
<b>Ingestion:</b>	Rinse mouth. Do not induce vomiting.
<b>Medical Conditions Aggravated by Exposure:</b>	Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged exposure to the substance can produce lung damage. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation

## Section 5 - Firefighting Measures

<b>Extinguishing Media:</b>	SMALL FIRE: Use dry chemical powder. LARGE FIRE: Use water spray, fog, or foam. Do not use water jet.
<b>Special Protective Equipment:</b>	In case of fire and/or explosion, do not breathe fumes. A self-contained breathing apparatus should be used to avoid inhalation of the product.
<b>Hazardous Combustion Products:</b>	These products are carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO, NO <sub>2</sub> , etc.

## Section 6 - Accidental Release Measures

**Personal Precautions:** Use personal protective equipment as described in section 8. Ventilation recommended.

**Environmental Precautions:** Do not allow to enter sewage system

## Section 7 - Handling and Storage

**General Handling Practices:** Avoid contact with skin and eyes. Use only in well-ventilated areas. Handle and open container with care. Do not breathe gas/fumes/vapor/spray. Local exhaust required. Use personal protective equipment described in section 8

**Handling Precautions:** Wear gloves, goggles and protective clothing to prevent contact with product.

**Storage Requirements:** Keep container tightly closed in a cool, well-ventilated place. Keep container dry. Keep away from heat. Keep from freezing. Store material at temperatures between 36F and 120F. Do not store containers in direct sunlight

## Section 8 - Precautions to Control Exposure / Personal Protection

Component	Source	Type	Value	Remarks
Acetone	OSHA	TWA	1000 ppm	
Acetone	ACGIH	TWA	500 ppm	
Dibutyl Phthalate	OSHA	TLV	5 mg/m <sup>3</sup>	TWA
Dibutyl Phthalate	ACGIH	PEL	5 mg/m <sup>3</sup>	TWA
Methyl Acetate	ACGIH	TLV	250 ppm	STEL
Methyl Acetate	ACGIH	TLV	200 ppm	TWA
Methyl Acetate	OSHA	PEL	200 ppm	TWA
Parachlorobenzotrifluoride (PCBTF)	Manufacturer	TWA	20 ppm	
Xylene	OSHA	PEL	100 ppm	TWA
Xylene	ACGIH	TLV	100 ppm	TWA
Xylene	ACGIH	TLV	150 ppm	STEL

### Personal Protective Equipment (PPE):

**Eye / Face Protection:** Chemical splash goggles (ANSI Z 87.1 or approved equivalent).

**Skin Protection:** Impervious rubber gloves.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**Hygienic Measures:** Wash hands before eating, smoking or using the bathroom.

**Engineering Controls:** Adequate to keep exposure limits below those listed in section II

**HMIS Personal Protection:** G



## Section 9 - Physical and Chemical Properties

**Appearance:** Liquid  
**Color:** Black  
**Odor:** Fruity odor  
**Odor Threshold:** Not determined  
**pH:** Not determined  
**Melting Point:** Not available  
**Freezing Point:** Not available  
**Boiling Point:** Not available  
**Boiling Range:** Not available  
**Flash Point:** 21 C (69 F)  
**Evaporation Rate:** Faster than n-Butyl Acetate  
**Flammability:** Not available  
**Upper Flammability Limit:** Not available  
**Lower Flammability Limit:** Not available  
**Vapor Pressure:** Not available  
**Vapor Density:** Heavier than air  
**Specific Gravity:** 1.07  
**Solubility in Water:** Not available  
**Partition Coefficient:** Not available  
**Autoignition Temperature:** Not available  
**Decomposition Temperature:** Not available  
**Viscosity:** Not available  
**Percent Volatiles:** 75 - 80%  
**Volatile Organic Compounds (VOC's):** 334 g/l (2.79 lb./gal)

---

## Section 10 - Stability and Reactivity

---

**Chemical Stability:** Stable

**Conditions to Avoid:** Excessive heat and freezing temperatures

**Incompatible Materials:** Oxidizing agents, alkalis and high temperatures.

**Hazardous Decomposition Products:** Chlorine, hydrogen chloride (hydrochloric acid), phosgene

**Hazardous Polymerization:** Will not occur

---

## Section 11 - Toxicological Information

---

**Sensitization:** No sensitizing effects known

---

## Section 12 - Ecological Information

---

---

## Section 13 - Disposal Considerations

---

**Disposal Method:** Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not contaminate lakes, streams or other water supply.

**Container Disposal:** Disposal must be made according to official regulations

---

## Section 14 - Transport Information

---

## DOT

**Proper Shipping Name:** Paint  
**Hazard Class:** 3  
**Identification Number:** UN1263  
**Packing Group:** II

## IMDG (Maritime transport)

**Proper Shipping Name:** Paint  
**IMDG Class:** 3  
**UN Number:** UN1263  
**Label:** 3  
**EMS Number:** F-E, S-E  
**Marine Polutant?:** No

## IATA (Air transport)

**Proper Shipping Name:** Paint  
**ICAO / IATA Class:** 3  
**UN / ID Number:** UN1263  
**Label:** 3  
**Packing Group** II

---

## Section 15 - Regulatory Information

---

Superfund Amendments and Reauthorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986)  
Sections 311 and 312

Immediate (Acute) Health Hazard: Not available  
Delayed (Chronic) Health Hazard: Not available  
Fire Hazard: Not available  
Reactive Hazard: Not available  
Sudden Release of Pressure: Not available

---

**The following lists hazardous components and the regulatory lists for which they are required to be reported.**

---

**Component:** Acetone

**CAS:** 67-64-1

**Amount:** 5 - 10%

Acetone is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.

---

**Component:** Dibutyl Phthalate

**CAS:** 87-74-2

**Amount:** 1 - 5%

Dibutyl Phthalate is on the California Prop 65 Cancer list.

---

**Component:** Xylene

**CAS:** 1330-20-7

**Amount:** 5 - 7%

Xylene is listed with Pennsylvania Right to Know.

Xylene is listed with the Environmental Protection Agency (EPA) as a possible carcinogen.

Xylene is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.


---

#### HMIS Rating (0 - 4)

<b>HEALTH</b>	<b>2</b>	Health = 2
<b>FIRE</b>	<b>3</b>	Fire = 3
<b>PHYSICAL</b>	<b>1</b>	Physical = 1
<b>PERSONAL PROTECTION</b>	<b>G</b>	Personal Protection = G

---

#### NFPA Ratings



## Section 16 - Other Information

---

### Legend

ACGIH	American Conference of Governmental Hygienists
CAS	Chemical Abstract Service
CFR	Code of Federal Regulations
EPA	Environmental Protection Agency
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
LTEL	Long Term Exposure Limit
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OEL	Occupational Exposure Limit

---

OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
REL	Recommended Exposure Level
SARA	Superfund Amendment and Reauthorization Act
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
VOC	Volatile Organic Compounds

---

## **DISCLAIMER**

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.