



Bumper & Cladding Coat Adhesion Primer Warranty

Polyvance guarantees that Bumper & Cladding Coat Adhesion Primer (3600 & 3610 series) or will adhere to raw, unprimed TPO plastic bumpers for as long as the consumer owns the vehicle. Bumper & Cladding Coat is guaranteed not to peel from properly prepared plastic surfaces. See below for preparation instructions, terms, and conditions.

A copy of this completed document must be retained with the repair file and submitted with any claims.

VIN _____ Vehicle Yr./Make/Model _____

Vehicle Owner's Name: _____

Bumper & Cladding Coat Part No. and Batch Number: _____

Batch Number of 1000 Super Clean Used: _____

Bumper & Cladding Coat Applied By: _____ Date Applied: _____

This warranty is made in lieu of and excludes any and all other warranties express or implied.

Polyvance, 1128 Kirk Rd, Rainsville AL 35986-6028 USA
phone: 800-633-3047 fax: 800-824-0087 e-mail: info@polyvance.com

Preparation and Application Instructions

The proper adhesion of a paint film onto a surface is largely dependent on surface preparation, especially on low-surface-energy plastics like TPO. Bumper & Cladding Coat is guaranteed to adhere to clean, unprimed raw TPO plastic. The surface must be cleaned according to the following instructions in order for this Warranty to be in effect.

1. When painting new, unprimed replacement TPO bumpers, clean the surface with Polyvance's 1000 Super Prep or 1001 EcoPrep plastic cleaner. Spray the material on in a heavy, wet coat, then wipe off in one direction with a clean cloth, turning cloth with each wipe to expose a clean surface.
2. Apply Bumper & Cladding Coat Adhesion Primer per label instructions. Allow to dry 60 minutes at 75°F or 15 minutes at 130°F before topcoating.
3. Apply approved base-clear topcoat system. See updated list of approved systems on Polyvance's website. Bumper & Cladding Coat is not to be topcoated with urethane single stage paint, catalyzed basecoat paints or 2K urethane primer surfacers.

Terms & Conditions

If properly prepared and applied, Bumper & Cladding Coat is guaranteed not to peel from TPO plastic bumpers, side cladding, and trim for as long as the consumer owns the vehicle. This warranty covers reasonable costs for labor, parts, and materials and excludes consequential or incidental damages to a maximum of \$300 per occur-

rence. This warranty is made in lieu of and excludes any and all other warranties express or implied. This warranty is not transferable in the event the vehicle is sold or traded to another individual or company.

Guarantee Exclusions

- Paint peeling resulting from improperly prepared surface.
- Paint peeling resulting from an underlying refinish or repair material. Bumper & Cladding Coat is guaranteed only when applied directly to the TPO plastic part with no underlying coating.
- Paint delaminations smaller than 1/4" square which result from rock chip damage.
- Any delamination resulting from physical damage or abrasion.

Guarantee Remedy

Polyvance will compensate the collision repair center directly for any losses covered by this warranty. To submit a claim, mail or fax a copy of this completed warranty certificate along with a clear photograph of the paint delamination to the Technical Support Manager at Polyvance. If validated, Polyvance will reimburse the collision repair center for labor, parts, and materials required to complete the repair to a maximum of \$300. *Note:* Polyvance cannot control the application of the product in the shop and, as such, reserves the right to rescind this warranty at any time if the volume of claims is determined to be excessive.