

Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2025-04-08

Section 1 - Product and Company Information

Product Name: Plastic Magic (gallon)

Product Part Number(s): 1050-1,

Recommended Use: A surface modifier that eliminates the paint peeling problems on automotive plastics.

COMPANY IDENTIFICATION:

Polyvance
1128 Kirk Rd.
Rainsville, AL 35986

Information email: info@polyvance.com

EMERGENCY TELEPHONE NUMBER:

24 Hour Emergency contact: Chemtrec: 1-800-424-9300
Outside US: 703-527-3887

Customer Information Number: 256-638-4103 (7AM - 4PM (CST) M-F)

Section 2 - Hazards Identification

Appearance: Clear liquid

Odor: Petroleum odor

Hazard Statement:

WARNING! Fire or projection hazard. Flammable liquid and vapor. Pressurized container: may burst if heated. May cause an allergic skin reaction. Causes eye irritation.

Signal Word: WARNING!

Signal Word Hazard: Flammable Liquid

GHS Physical Hazard Pictogram	GHS Health Hazard Pictogram(s)	GHS Environmental Hazard Pictogram
 Flammable	 Irritant	Not Applicable

GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Physical	H204	Fire or projection hazard
Physical	H226	Flammable liquid and vapor
Physical	H229	Pressurized container: may burst if heated
Health	H317	May cause an allergic skin reaction
Health	H320	Causes eye irritation

Precautionary Statement:

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces - No smoking. IF ON SKIN: Wash with soap and water.

GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
General	P102	Keep out of reach of children
General	P103	Read label before use
Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
Response	P302+352	IF ON SKIN: Wash with soap and water

Potential Health Effects

Eye Contact:	Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and asphyxiation.
Skin Absorption:	Moderate irritation, redness, blurred vision.
Inhalation:	Dizziness, breathing difficulty, headaches, and loss of coordination.
Ingestion:	Gastrointestinal irritation, vomiting, diarrhea.

Section 3 - Composition / Information on Ingredients

Component	CAS #	ENIECS	REACH Reg. No.	Amount
Chlorinated Polyolefin	24937-78-8			0 - 2%
Heptane	142-82-5			45 - 50%
Methyl Ethyl Ketone	78-93-3			1 - 2%
Toluene	108-88-3			45-50%
Resin	Proprietary			0 - 2%

Section 4 - First Aid Measures

Eye Contact:	Immediately flush eyes with excess water for 15 minutes, lifting lower and upper eyelids occasionally.
Skin Contact:	Immediately flush skin with excess water for 15 minutes removing contaminated clothing.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration.
Ingestion:	Call Poison Control immediately. Aspiration hazard. Rinse mouth with cold water. Give victim 1-2 tbsp of activated charcoal mixed with 8 oz. of water.
Medical Conditions Aggravated by Exposure:	Bronchitis, CNS disorders, allergies, nausea.

Section 5 - Firefighting Measures

Extinguishing Media:	Foam, dry chemical, water fog
Unusual Fire or Explosion Hazards:	Handle as a flammable liquid. Vapors form an explosive mixture in air between the lower and upper explosive limits which can be ignited by many sources such as pilot lights, open flames, electric motors and switches.
Fire Fighting Procedures:	Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as a fog to keep nearby containers cool.

Section 6 - Accidental Release Measures

Personal Precautions:	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all ignition sources and ventilate area.
------------------------------	--

Methods For Clean Up: Remove all sources of ignition. Allow volatile portion to evaporate completely. Avoid breathing vapors and remove with inert absorbent.

Methods for Containment: Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not contaminate lakes, streams or other water supply.

Section 7 - Handling and Storage

General Handling Practices: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid spontaneous combustion of contaminated rags or other ignitable material. Keep out of reach of children.

Handling Precautions: Use with adequate ventilation and do not breathe dust or vapor. Avoid contact with skin, eyes, or clothing. Wash hands thoroughly after handling.

Storage Requirements: Do not store near heat, sparks or flame. Store in well ventilated area. Keep closure tight and container upright to prevent leakage. Do not puncture or incinerate. Do not spray near fire or open flames.

Section 8 - Precautions to Control Exposure / Personal Protection

Component	Source	Type	Value	Remarks
Heptane	ACGIH	TLV	500 ppm	STEL
Heptane	ACGIH	TLV	400 ppm	TWA
Heptane	OSHA	PEL	500 ppm	TWA
Methyl Ethyl Ketone	ACGIH	STEL	300ppm 885mg/m3	
Methyl Ethyl Ketone	ACGIH	TWA	200ppm 590mg/m3	
Methyl Ethyl Ketone	ACGIH	TWA	200ppm 590mg/m3	
Methyl Ethyl Ketone	NIOSH	STEL	300ppm 885mg/m3	
Methyl Ethyl Ketone	NIOSH	TWA	200ppm 590mg/m3	
Methyl Ethyl Ketone	OSHA	TWA	200 ppm 590 mg/m3	
Toluene	ACGIH	TLV-TWA	50 ppm	
Toluene	OSHA	Ceiling	300 ppm	
Toluene	OSHA	STEL	150 ppm	
Toluene	OSHA	PEL	100 ppm	

Personal Protective Equipment (PPE):

Eye / Face Protection: Goggles or side-shielded safety glasses.

Skin Protection: Neoprene or butyl rubber gloves.

Respiratory Protection: Use of a NIOSH approved chemical/mechanical filter, designed to remove a combination of particles and vapors.

Hygienic Measures: Wash hands before eating, smoking or using the washroom.

Other Protection Measures: To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Wash contaminated clothing before reuse.

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s)

HMIS Personal Protection: J



Section 9 - Physical and Chemical Properties

Appearance:	Clear liquid
Color:	Clear, colorless liquid.
Odor:	Mild odor.
Odor Threshold:	Not determined
pH:	Not determined
Melting Point:	Not available
Freezing Point:	Not available
Boiling Point:	180.0
Boiling Range:	Not available
Flash Point:	23 F (-5 C)
Evaporation Rate:	5.8 (butyl acetate = 1)
Flammability:	Not available
Upper Flammability Limit:	11.5%
Lower Flammability Limit:	1%
Vapor Pressure:	Not available
Vapor Density:	Heavier than air
Specific Gravity:	0.80
Solubility in Water:	Not Soluble
Partition Coefficient:	Not available
Autoignition Temperature:	434 F (223 C)
Decomposition Temperature:	Not available
Viscosity:	Not available
Percent Volitiles:	97%
Volatile Organic Compounds (VOC's):	6.32 lb./gal (757 g/l)

Section 10 - Stability and Reactivity

Chemical Stability:	Stable
Conditions to Avoid:	Excessive heat, poor ventilation, open flames, sources of sparks.
Incompatible Materials:	Alkaline materials, strong acids, and oxidizing materials.
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide, various hydrocarbons, oxides of nitrogen, chlorine and possibly acrolein.
Hazardous Polymerization:	Will Not Occur

Section 11 - Toxicological Information

Ingestion Toxicity:	Not available
Skin Absorption:	Not available
Inhalation:	Not available
Sensitization:	Not available
Acute Dose:	Not available

Repeated Dose: Not available
Carcinogenicity: Not available
Corrosivity: Not available
Neurological: Not available
Reproductive: Not available
Genetic: Not available
Developmental: Not available
Eye Irritation: Not available
Skin Irritation: Not available
Target Organs: Not available

Section 12 - Ecological Information

EcoToxicity: Toxic to terrestrial and aquatic plants and animals. Do not release to the environment.

Section 13 - Disposal Considerations

Disposal Method: Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not contaminate lakes, streams or other water supply.

Container Disposal: Disposal must be made according to official regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Paint related material
Hazard Class: 3
Identification Number: UN1263
Packing Group: II
DOT Labeling: Flammable Liquid
Additional DOT Shipping Information: NMFC 149980 Sub 03 Freight Class 60

IMDG (Maritime transport)

Proper Shipping Name: PAINT RELATED MATERIAL
IMDG Class: 3
UN Number: UN1263
Label: Flammable Liquid
EMS Number: F-E, S-E

IATA (Air transport)

Proper Shipping Name: Paint related material

ICAO / IATA Class: 3

UN / ID Number: UN1263

Label: Flammable Liquid

Packing Group II

Section 15 - Regulatory Information

Superfund Amendments and Reauthorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986)
Sections 311 and 312

Immediate (Acute) Health Hazard: Not available

Delayed (Chronic) Health Hazard: Not available

Fire Hazard: Not available

Reactive Hazard: Not available

Sudden Release of Pressure: Not available

The following lists hazardous components and the regulatory lists for which they are required to be reported.

Component: Chlorinated Polyolefin

CAS: N/A

Amount:

Component: Heptane

CAS: 142-82-5

Amount: 45-50%

Component: Methyl Ethyl Ketone

CAS: 78-93-3

Amount: 1 %

Component: Toluene

CAS: 108-88-3

Amount: 45-50%

Toluene is on the California Prop 65 Reproductive list.

Toluene is listed with the Illinois toxic substances disclosure to employee act.

Toluene is listed with Massachusetts Right to Know.

Toluene is listed with Minnesota Right to Know.

Toluene is listed with New Jersey Right to Know.

Toluene is listed with Pennsylvania Right to Know.

Toluene is listed with Rhode Island Right to Know.

is listed with the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

Component: Vinyl Acetate Copolymer


CAS: 24937-78-8

Amount:

HMIS Rating (0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
PHYSICAL	1	Physical = 1
PERSONAL PROTECTION	J	Personal Protection = J

NFPA Ratings



Section 16 - Other Information

Legend

ACGIH	American Conference of Governmental Hygienists
CFR	Code of Federal Regulations
DFG	Deutsche Forschungsgemeinschaft
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
MAK	Maximum Allowable Concentration (German)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
OEL	Occupational Exposure Limit
RCRA	Resource Conservation and Recovery Act
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.