Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2025-04-08

Section 1 - Product and Company Information

Product Name: Bumper and Cladding Coat Adhesion Primer

Product Part Number(s): 3601-4, 3601-1, 3601-4, 3602-1, 3602-4, 3604-1, 3604-4 **Recommended Use:** Primer applied to bumper covers to help paint to adhere

COMPANY IDENTIFICATION: EMERGENCY TELEPHONE NUMBER:

Polyvance 24 Hour Emergency contact: Chemtrec: 1-800-424-9300

Outside US: 703-527-3887

Rainsville, AL 35986

1128 Kirk Rd.

Information email: info@polyvance.com Customer Information Number: 256-638-4103 (7AM - 4PM (CST) M-F)

Section 2 - Hazards Identification

Appearance: Low viscosity, pourable liquid

Odor: Strong solvent odor

Hazard Statement:

WARNING! . Flammable liquid and vapor. May cause an allergic skin

reaction. Causes eve irritation.

Signal Word: WARNING! Signal Word Hazard: Flammable Liquid

GHS Physical Hazard Pictogram



Flammable

GHS Health Hazard Pictogram(s)



Irritant



Health Hazard

GHS Environmental Hazard Pictogram

Not Applicable

GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Physical	H226	Flammable liquid and vapor
Health	H317	May cause an allergic skin reaction
Health	H320	Causes eye irritation

Precautionary Statement:

. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Do not get in eyes, on skin, or on clothing. Explosion risk in case of fire. Store in a closed container.

GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
General	P102	Keep out of reach of children
General	P103	Read label before use

Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking	
Prevention	P262	Do not get in eyes, on skin, or on clothing	
Response	P372	Explosion risk in case of fire	
Storage	P404	Store in a closed container	

Potential Health Effects

Eye Contact: Moderate irritation, redness, blurred vison.

Skin Absorption: Moderate irritation, redness, dermatitis.

Inhalation: Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and

asphyxiation.

Ingestion: Gastrointestinal irritation, vomiting, diarrhea.

Section 3 - Composition / Information on Ingredients

Component	CAS#	ENIECS	REACH Reg. No.	Amount
Xylene	1330-20-7			3-7%
Toluene	108-88-3			5-15%
Propylene glycol monomethyl ether acetate	108-65-6			1-5%
Methyl Ethyl Ketone	78-93-3			3-7%
Methyl Acetate	79-20-9			15-25%
Resin blend	Proprietary			10-20%
1,2,4-Trimethylbenzene	95-63-6			0-3%
t-butyl acetate	540-88-5			20-40%
TiO2	13463-67-7			3-7%
Ethylbenzene	100-41-4			0-3%
Talc	1408-60-7			3-7%

Section 4 - First Aid Measures

Eye Contact: Flush with large amounts of water until all material is removed. If irritation persists, get medical

attention immediately.

Skin Contact: Wash with soap and water. Remove contaminated clothing and wash before re-use. Shower. If

irritation persists, see physician.

Inhalation: Move to fresh air. Artificial respiration if necessary. Consult physician immediately.

Ingestion: Do not induce vomiting. Consult physician immediately.

Medical Conditions

Aggravated by Exposure:

Bronchitis, CNS disorders, allergies, nausea

Section 5 - Firefighting Measures

Extinguishing Media: Fight source of fire. Dry chemical, carbon dioxide, chemical.

Unusual Fire or

None expected. Treat as solvent based flammable liquid.

Explosion Hazards:

Fire Fighting Use recommended extinguishing materials. If this material is involved in a fire, NIOSH approved self

Procedures: contained breathing apparatus should be worn.

Section 6 - Accidental Release Measures

Methods For Clean Up: Confine as much as possible. Dike and absorb with inert material such as vermiculite. Transfer to

containers for disposal.

Methods for

Dispose of in accordance with all Federal, State, and local ordinances.

Containment:

Practices:

Section 7 - Handling and Storage

General Handling

Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating

and inhaling the contents may be harmful or fatal. Avoid spontaneous combustion of

contaminated rags or other ignitable material. Keep out of reach of children.

Storage Requirements: Wear gloves, goggles and protective clothing to prevent contact with product. Store material at

temperatures between 36F (2 C) and 100F (38 C). Do not store containers in direct sunlight.

Section 8 - Precautions to Control Exposure / Personal Protection

ComponentSourceTypeValueRemarks1,2,4-TrimethylbenzeneACGIHTWA25 ppm1,2,4-TrimethylbenzeneNIOSHTWA25 ppm 125 mg/m3EthylbenzeneACGIHTWA20 ppmTLVEthylbenzeneACGIHSTEL125 ppmTLVEthylbenzeneNIOSHTWA00 ppm435 mg/m3EthylbenzeneOSHATWA100 ppmMethyl AcetateOSHATWA200 ppmMethyl AcetateACGIHTWA200 ppmTLVMethyl Ethyl KetoneOSHATWA200 ppmTLVMethyl Ethyl KetoneACGIHTWA200 ppmTLVMethyl Ethyl KetoneNIOSHTWA200 ppmTLVPropylene glycol monomethyl ether acetWEELTWA50 ppmTolueneACGIHTLV-TWA50 ppmTolueneOSHACeiling300 ppmTolueneOSHASTEL150 ppmTolueneOSHAPEL100 ppmTolueneOSHAPEL100 ppmTyleneOSHAPEL100 ppmTyleneACGIHTLV150 ppmTyleneACGIHTLV150 ppm		•			
1,2,4-TrimethylbenzeneNIOSHTWA 25 ppm 125 mg/m3EthylbenzeneACGIHTWA 20 ppmTLVEthylbenzeneACGIHSTEL 125 ppmTLVEthylbenzeneNIOSHTWA 00 ppm 435 mg/m3TUVEthylbenzeneOSHA TWA 100 ppmTUVMethyl AcetateOSHA TWA 200 ppmTLVMethyl AcetateACGIH TWA 200 ppmTLVMethyl Ethyl KetoneOSHA TWA 200 ppmTLVMethyl Ethyl KetoneACGIH TWA 200 ppmTLVMethyl Ethyl KetoneNIOSH TWA 200 ppmTLVPropylene glycol monomethyl ether acetWEEL TWA 50 ppmTOlueneTolueneACGIH TLV-TWA 50 ppmTOlueneTolueneOSHA Ceiling 300 ppmTolueneOSHA STEL 150 ppmTolueneOSHA PEL 100 ppmTWAXyleneOSHA PEL 100 ppmTWAXyleneACGIH TLV 150 ppmTUV	Component	Source	Type	Value	Remarks
EthylbenzeneACGIHTWA20 ppmTLVEthylbenzeneACGIHSTEL125 ppmTLVEthylbenzeneNIOSHTWA .00 ppm 435 mg/m3TUAEthylbenzeneOSHATWA100 ppmMethyl AcetateOSHATWA200 ppmTLVMethyl AcetateACGIHTWA200 ppmTLVMethyl Ethyl KetoneOSHATWA200 ppmTLVMethyl Ethyl KetoneACGIHTWA200 ppmTLVMethyl Ethyl KetoneNIOSHTWA200 ppmTLVPropylene glycol monomethyl ether acetWEELTWA50 ppmTOTolueneOSHACeiling300 ppmTOTolueneOSHASTEL150 ppmTOTolueneOSHAPEL100 ppmTWAXyleneOSHAPEL100 ppmTWAXyleneACGIHTLV150 ppmSTEL	1,2,4-Trimethylbenzene	ACGIH	TWA	25 ppm	
Ethylbenzene ACGIH STEL 125 ppm TLV Ethylbenzene NIOSH TWA .00 ppm 435 mg/m3 Ethylbenzene OSHA TWA 100 ppm Methyl Acetate OSHA TWA 200 ppm Methyl Acetate ACGIH TWA 200 ppm Methyl Ethyl Ketone OSHA TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone NIOSH TWA 200 ppm Propylene glycol monomethyl ether acet WEEL TWA 50 ppm Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	1,2,4-Trimethylbenzene	NIOSH	TWA	25 ppm 125 mg/m3	
Ethylbenzene NIOSH TWA 00 ppm 435 mg/m3 Ethylbenzene OSHA TWA 100 ppm Methyl Acetate OSHA TWA 200 ppm Methyl Acetate ACGIH TWA 200 ppm Methyl Ethyl Ketone OSHA TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone NIOSH TWA 200 ppm Propylene glycol monomethyl ether acet WEEL TWA 50 ppm Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Ethylbenzene	ACGIH	TWA	20 ppm	TLV
Ethylbenzene OSHA TWA 100 ppm Methyl Acetate OSHA TWA 200 ppm Methyl Acetate ACGIH TWA 200 ppm Methyl Ethyl Ketone OSHA TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm Methyl Ethyl Ketone NIOSH TWA 200 ppm Propylene glycol monomethyl ether acet WEEL TWA 50 ppm Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Ethylbenzene	ACGIH	STEL	125 ppm	TLV
Methyl Acetate OSHA TWA 200 ppm Methyl Acetate ACGIH TWA 200 ppm TLV Methyl Ethyl Ketone OSHA TWA 200 ppm Methyl Ethyl Ketone ACGIH TWA 200 ppm TLV Methyl Ethyl Ketone NIOSH TWA 200 ppm TLV Methyl Ethyl Ketone NIOSH TWA 200 ppm TLV Methyl Ethyl Ketone NIOSH TWA 50 ppm TLV Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Ethylbenzene	NIOSH	TWA	.00 ppm 435 mg/m3	
Methyl AcetateACGIHTWA200 ppmTLVMethyl Ethyl KetoneOSHATWA200 ppmTLVMethyl Ethyl KetoneACGIHTWA200 ppmTLVMethyl Ethyl KetoneNIOSHTWA200 ppmTLVPropylene glycol monomethyl ether acetWEELTWA50 ppmTolueneACGIHTLV-TWA50 ppmTolueneOSHACeiling300 ppmTolueneOSHASTEL150 ppmTolueneOSHAPEL100 ppmXyleneOSHAPEL100 ppmTWAXyleneACGIHTLV150 ppmSTEL	Ethylbenzene	OSHA	TWA	100 ppm	
Methyl Ethyl Ketone Methyl Ethyl Ketone ACGIH TWA 200 ppm TLV Methyl Ethyl Ketone NIOSH TWA 200 ppm TLV Methyl Ethyl Ketone NIOSH TWA 50 ppm Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV TLV TSO ppm TWA STEL	Methyl Acetate	OSHA	TWA	200 ppm	
Methyl Ethyl KetoneACGIHTWA200 ppmTLVMethyl Ethyl KetoneNIOSHTWA200 ppmPropylene glycol monomethyl ether acetWEELTWA50 ppmTolueneACGIHTLV-TWA50 ppmTolueneOSHACeiling300 ppmTolueneOSHASTEL150 ppmTolueneOSHAPEL100 ppmXyleneOSHAPEL100 ppmTWAXyleneACGIHTLV150 ppmSTEL	Methyl Acetate	ACGIH	TWA	200 ppm	TLV
Methyl Ethyl KetoneNIOSHTWA200 ppmPropylene glycol monomethyl ether acetWEELTWA50 ppmTolueneACGIHTLV-TWA50 ppmTolueneOSHACeiling300 ppmTolueneOSHASTEL150 ppmTolueneOSHAPEL100 ppmXyleneOSHAPEL100 ppmTWAXyleneACGIHTLV150 ppmSTEL	Methyl Ethyl Ketone	OSHA	TWA	200 ppm	
Propylene glycol monomethyl ether acet WEEL TWA 50 ppm Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Methyl Ethyl Ketone	ACGIH	TWA	200 ppm	TLV
Toluene ACGIH TLV-TWA 50 ppm Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Methyl Ethyl Ketone	NIOSH	TWA	200 ppm	
Toluene OSHA Ceiling 300 ppm Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Propylene glycol monomethyl ether acet	WEEL	TWA	50 ppm	
Toluene OSHA STEL 150 ppm Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Toluene	ACGIH	TLV-TWA	50 ppm	
Toluene OSHA PEL 100 ppm Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Toluene	OSHA	Ceiling	300 ppm	
Xylene OSHA PEL 100 ppm TWA Xylene ACGIH TLV 150 ppm STEL	Toluene	OSHA	STEL	150 ppm	
Xylene ACGIH TLV 150 ppm STEL	Toluene	OSHA	PEL	100 ppm	
•	Xylene	OSHA	PEL	100 ppm	TWA
Xviene ACGIH TLV 100 ppm TWA	Xylene	ACGIH	TLV	150 ppm	STEL
Aylene 100 ppm 1 vvA	Xylene	ACGIH	TLV	100 ppm	TWA

Personal Protective Equipment (PPE):

Eye / Face Protection: Chemical splash goggles (ANSI Z 87.1 or approved equivalent.)

Skin Protection: Impervious rubber gloves.

RespiratoryProtection: None required if adequate ventilation is provided.

Hygenic Measures: Wash hands before eating, smoking or using the bathroom.Other Protection Wear protective clothing to prevent contact with products.

Measures:

Adequate to keep exposure limits below those listed in section II

HMIS Personal G

Engineering Controls:

Protection:







Section 9 - Physical and Chemical Properties

Appearance: Opaque, medium viscosity, pourable liquid

Odor Threshold: Not determined

pH: Not determined

Melting Point: Not available Freezing Point: Not available

less than 140 C

Boiling Range: Not available **Flash Point:** 7 C (44 F)

Evaporation Rate: Not available **Flammability:** Not available

Upper Flammability Limit: N/A **Lower Flammability Limit:** N/A

Vapor Pressure: Not available
Vapor Density: Heavier than air

Specific Gravity: 0.924
Solubility in Water: stable

Partition Coefficient: Not available
Autoignition Temperature: Not available
Decomposition Temperature: Not available

Viscosity: Not available

Volitile Organic Compounds 6.30 lb./gal (754 g/l)

(VOC's):

Section 10 - Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Excessive heat and freezing temperatures. **Incompatible Materials:** None known to cause dangerous condition.

Hazardous Decomposition Carbon monoxide, carbon dioxide, and unidentified organic compounds.

Products:

Hazardous Polymerization: Will not occur.

Section 11 - Toxicological Information

Section 12 - Ecological Information

Section 13 - Disposal Considerations

Disposal Method: Dispose of in accordance with all Federal, State, and local ordinances.

ContainerDisposal: Disposal must be made according to official

regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Paint Flammable Liquid

Hazard Class: 3

Identification Number: UN1263

Packing Group: ||

IMDG (Maritime transport)

Proper Shipping Name: Paint Flammable Liquid

IMDG Class: 3 Flammable Liquid

UN Number: UN1263

Marine Polutant?: No

IATA (Air transport)

Proper Shipping Name: Paint Flammable Liquid

ICAO / IATA Class: 3 Flammable Liquid

UN / ID Number: UN1263

Packing Group ||

Section 15 - Regulatory Information

Superfund Amendments and Reathorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986)

Sections 311 and 312

Immediate (Acute) Health Hazard: Not available
Delayed (Chronic) Health Hazard: Not available
Fire Hazard: Not available
Reactive Hazard: Not available
Sudden Realease of Pressure: Not available

The following lists hazardous components and the regulatory lists for which they are required to be reported.

Component: 1,2,4-Trimethylbenzene

CAS: 95-63-6 **Amount:** 1%

Component: 1-methoxy-2acetoypropane

CAS: 108-65-6 **Amount:** 3%

Component: Ethylbenzene

CAS: 100-41-4 **Amount:** 1%

Ethylbenzene is on the California Prop 65 Cancer list. Ethylbenzene is listed with Massachusetts Right to Know. Ethylbenzene is listed with Pennsylvania Right to Know.

Component: Methyl Acetate

CAS: 79-20-9 **Amount**: 20%

Methyl Acetate is listed with Massachusetts Right to Know. Methyl Acetate is listed with Pennsylvania Right to Know.

Component: Methyl Ethyl Ketone

CAS: 78-93-3 **Amount**: 5%

Component: Resin blend

CAS: Proprietary
Amount: 15%

Component: t-butyl acetate

CAS: 540-88-5 **Amount:** 30%

t-butyl acetate is listed with Massachusetts Right to Know.

t-butyl acetate is listed with Minnesota Right to Know.

t-butyl acetate is listed with New Jersey Right to Know.

t-butyl acetate is listed with Pennsylvania Right to Know.

t-butyl acetate is listed with Rhode Island Right to Know.

is listed with the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

Component: Tio2 CAS: 13463-67-7 Amount: 5% Component: Toluene

CAS: 108-88-3 **Amount**: 10%

Toluene is on the California Prop 65 Reproductive list.

Toluene is listed with the Illinois toxic substances disclosure to employee act.

Toluene is listed with Massachusetts Right to Know.

Toluene is listed with Minnesota Right to Know.

Toluene is listed with New Jersey Right to Know.

Toluene is listed with Pennsylvania Right to Know.

Toluene is listed with Rhode Island Right to Know.

is listed with the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

Component: Xylene CAS: 1330-20-7 Amount: 10-20%

Xylene is listed with Pennsylvania Right to Know.

Xylene is listed with the Envronmental Protection Agency (EPA) as a possible carcinogen.

Xylene is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.

Xylene is listed with American Conference on Governmental Industrial Hygenists (ACGIH) as a possible

carcinogen.

HMIS Rating (0 - 4)




Health = 2 Fire = 3

Physical = 1

Personal Protection = G

NFPA Ratings



Section 16 - Other Information

Legend

ACGIH American Conference of Governmental Hygenists

CFR Code of Federal Regulations

DFG Deutsche Forschungsgemeinschaft

HMIS Hazardous Materials Identification System
IARC International Agency for Research on Cancer
MAK Maximum Allowable Concentration (German)

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

OEL Occupational Exposure Limit

RCRA Resource Conservation and Recovery Act

STEL Short Term Exposure Limit
TLV Threshold Limit Value
TWA Time Weighted Average

DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein my be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.