

3010

Waterborne Black Flexible Primer-Surfacer

3010 Waterborne Black Flexible Primer-Surfacer is a high-build, easy sanding undercoat for flexible plastics, SMC, fiberglass, or metal.

Benefits:

- Waterborne formulation meets all federal, state, and local VOC regulations, including Southern California. (VOC = 90 g/liter or 0.75 lb/gal)
- High build formulation hides 220 grit sandscratches with ease.
- Beautiful low-sheen flat black appearance.
- Sands like chalk -- doesn't load the sandpaper even when dry sanding.
- May be topcoated with any type of paint system.
- Flexible -- will not crack when bent 60 degrees over a 1-1/2 inch radius.

Application:

- Clean the plastic prior to repair and refinishing with 1000 Super Clean Plastic Cleaner.
- Spray any raw plastic areas to be primed with 1050 Plastic Magic adhesion promoter.
- Stir 3010 Waterborne Black Primer Surfacer. Ready to spray - do not thin. Using 30 - 35 psi at the gun, apply two medium wet coats with 10-15 minutes of flash time between coats. Allow final coat 30-60 minutes dry time before sanding (depends on film thickness and climate conditions).



3010 Waterborne Black Flexible Primer Surfacer

Dimensions: **3010-1**, 1 U.S. Gallon (3.785 liters)
6.6 in diameter x 7.5 in height
(16.8cm diameter x 19.1cm height)

3010-4, 1 U.S. Quart (946 ml)
4.3 in diameter x 4.9 in height
(10.9cm diameter x 12.4cm height)

3010-5, 5 U.S. Gallons (18.9 liters)
12.5 in diameter x 15.5 in height
(31.8cm diameter x 39.4cm height)

Weight: **3010-1** 10.6 lb (4.8 kg)

3010-4 2.7 lb (1.2 kg)

3010-5 53 lb (24 kg)